

SLC Series
Eccentric Disc Pump

Where Innovation Flows

Seal-less
Solutions for
Chemical Applications

The new generation of **Mouvex**[®] Eccentric Disc Pumps,
designed to provide premium performance and ultimate safety in
chemical and industrial applications.



Benefits:

- Self-priming
- Seal-less Design
- Low Shear Rate
- Consistent Flow Rate
- Strong Suction and Discharge Pressure



Design:

- **Features and Benefits:** Unique seal-less design features a double stainless steel bellows which ensures durability, safety and product containment. The SLC Series provides very high suction and discharge pressures which allows it to self-prime and fully strip lines, maximizing product recovery.
- The SLC can run dry for up to 5 minutes, and the self-compensating eccentric disc principle provides consistent flow rates over a long period of time. The flow rate is extremely accurate even at low speeds.
- There are fewer moving parts, which results in reduced maintenance and downtime.

Application:

- Suitable for most chemical and industrial transfer applications, even those that require consistent non-pulsing flow and gentle fluid handling (low shear rates).

Operation:

- **Principle:** Eccentric Disc, positive displacement
- **Installation:** Can be base mounted or cart mounted for mobility

Description of Construction:

- All Stainless Steel construction
- Shaft sealed by double Stainless Steel bellows
- O-ring seals in FKM or FEP

Options:

- Bellows Monitoring System (BMS)
- ISO PN 20 flanges
- ISO PN 16 flanges
- Heating Jacket

Model	Max Speed	Max. Flow Rate	Max. Diff. Pressure
SLC4	750 rpm	4 m ³ /h (17.6 gpm)	10 bar (145 psi)
SLC8	750 rpm	8 m ³ /h (35.2 gpm)	6 bar (87 psi)



ZI la Plaine des Isles
 2 rue des Caillottes • F-89000 AUXERRE - FRANCE
 O: + 33.3.86.49.86.30 • F: + 33.3.86.46.42.10
 contact@mouvex.com
 www.mouvex.com



Authorized PSG Partner: